

KENOVEL[®]

Compensateur SANITAIRE* Type 2S - Certification WRAS



DN20 - DN300



DN	L	Mouvement axial		Mouvement latéral	Mouvement angulaire	Pression max	Température max	Aspiration
		Compression	Elongation					
mm/pouce	mm	mm	mm	mm	mm	T°C Ambiante Bar	+80°C Bar	Sans anneau mmCE
20 / ¾"	120	15	10	15	20°	16	6,5	650
25 / 1"	120	15	10	15	20°	16	6,5	650
32 / 1¼"	175	25	15	20	30°	16	6,5	650
40 / 1½"	175	25	15	20	30°	16	6,5	650
50 / 2"	175	25	15	20	30°	16	6,5	650
65 / 2½"	175	25	15	20	30°	16	6,5	650
80 / 3"	175	25	15	20	30°	16	6,5	650
100 / 4"	225	30	20	25	30°	16	6,5	650
125 / 5"	225	30	20	25	30°	16	6,5	650
150 / 6"	225	30	20	25	30°	16	6,5	650
200 / 8"	325	40	25	30	30°	16	6,5	650
250 / 10"	325	40	25	30	30°	16	6,5	650
300 / 12"	325	40	25	30	30°	16	6,5	650

* Compensateur en caoutchouc EPDM WRAS (eau potable, eau, eau chaude, eau froide, eau de mer, air et acide faible), les brides sont en acier galvanisé