

# KENOVEL<sup>®</sup>

## Compensateur ARCADE<sup>®</sup> Type S brides tournantes

DN25 - DN1200



DN	Largeur	Mouvement axial		Mouvement Latéral	Mouvement Angulaire	Pression max	Aspiration
		Compression	Elongation				
mm/pouce	mm	mm	mm	mm	mm	Bar	mmCE
25 / 1"	90/130/150	10	6	10	25°	16	760
32 / 1"¼	90/130/150	10	6	10	25°	16	760
40 / 1"½	90/130/150	10	6	10	25°	16	760
50 / 2"	130/150/200	10	6	10	25°	16	760
65 / 2"½	130/150/200	15	6	12	25°	16	760
80 / 3"	130/150/200	15	8	12	15°	16	760
100 / 4"	130/150/200	20	12	16	15°	16	760
125 / 5"	130/150/200	20	12	16	15°	16	760
150 / 6"	130/150/200	20	12	16	15°	16	760
200 / 8"	130/150/200	30	30	16	8°	16	760
250 / 10"	130/150/200	30	30	25	8°	16	760
300 / 12"	130/200/250	30	30	25	8°	16	760
350 / 14"	130/200/250	30	30	25	8°	10	760
400 / 16"	200/250/265	30	30	25	8°	10	760
450 / 18"	200/250/265	30	30	25	8°	10	760
500 / 20"	200/250/300	30	30	25	8°	10	760
600 / 24"	200/250/300	40	40	25	8°	10	760
700 / 28"	260	40	40	30	3°	10	760
750 / 30"	260/300	40	40	30	3°	10	760
800 / 32"	260	40	40	30	3°	10	760
900 / 36"	260	40	40	30	3°	10	760
1000 / 40"	260/300	40	40	30	3°	10	760
1050 / 42"	350	40	20	18	2°	10	760
1100 / 44"	350	40	20	18	2°	10	760
1150 / 46"	350	40	20	18	2°	10	760
1200 / 48"	350	40	20	18	2°	10	760