

KENOVEL[®]

Compensateur Air-Eau* Style 10

DN25 - DN700



| DN | L | Mouvement axial | | Mouvement latéral | Mouvement angulaire | Pression max | Température max | | Aspiration |
|------------|-----|-----------------|------------|-------------------|---------------------|--------------|-----------------|--------|------------|
| | | Compression | Elongation | | | | T°C Ambiante | +115°C | |
| mm/pouce | mm | mm | mm | mm | mm | Bar | Bar | mmCE | |
| 25 / 1" | 95 | 9 | 6 | 9 | 15° | 16 | 2 | 750 | |
| 32 / 1¼" | 95 | 10 | 6 | 9 | 15° | 16 | 2 | 750 | |
| 40 / 1½" | 95 | 10 | 6 | 9 | 15° | 16 | 2 | 750 | |
| 50 / 2" | 105 | 10 | 7 | 10 | 15° | 16 | 2 | 750 | |
| 65 / 2½" | 115 | 13 | 8 | 12 | 15° | 16 | 2 | 750 | |
| 80 / 3" | 130 | 15 | 8 | 12 | 15° | 16 | 2 | 750 | |
| 100 / 4" | 135 | 19 | 12 | 15 | 15° | 16 | 2 | 750 | |
| 125 / 5" | 170 | 19 | 12 | 15 | 15° | 16 | 2 | 750 | |
| 150 / 6" | 180 | 20 | 12 | 15 | 10° | 16 | 2 | 750 | |
| 200 / 8" | 205 | 20 | 12 | 22 | 10° | 16 | 2 | 750 | |
| 250 / 10" | 240 | 28 | 16 | 22 | 10° | 16 | 2 | 750 | |
| 300 / 12" | 260 | 28 | 16 | 25 | 10° | 16 | 2 | 750 | |
| 350 / 14" | 265 | 28 | 16 | 25 | 10° | 8 | 2 | 500 | |
| 400 / 16" | 265 | 28 | 16 | 25 | 10° | 8 | 2 | 500 | |
| 450 / 18" | 265 | 28 | 16 | 25 | 10° | 8 | 2 | 500 | |
| 500 / 20" | 265 | 28 | 16 | 25 | 10° | 8 | 2 | 500 | |
| 600 / 24" | 265 | 28 | 16 | 25 | 10° | 8 | 2 | 500 | |
| 700 / 28" | 260 | 28 | 16 | 25 | 10° | | 2 | | |
| 800 / 32" | 260 | 28 | 16 | 25 | 10° | | 2 | | |
| 900 / 36" | 260 | 28 | 16 | 25 | 10° | | 2 | | |
| 1000 / 40" | 260 | 28 | 16 | 25 | 10° | | 2 | | |
| 1200 / 48" | 260 | 28 | 16 | 25 | 10° | | 2 | | |
| 1400 / 56" | 300 | 28 | 16 | 25 | 10° | | 2 | | |
| 1600 / 64" | 300 | 28 | 16 | 25 | 10° | | 2 | | |

* Compensateur en caoutchouc EPDM pour eau de chauffage (eau, eau chaude, eau froide, eau de mer, air et acide faible), les brides peuvent être en fonte zinguée